


# tempio

Rustikotta skin

## Technical data sheet



### Rustikotta Classic

RKC130600 225x400x13mm

For use in coating vertical façades

### Colours

EK1005 Red flamed · EK1009 Light Grey Flamed · EK1014 White September  
EK1024 Antique Moss · EK1027 Black Oxid · EK1038 Tampico · EK1051 New Black

Water absorption	EN ISO 10545-3	Group All <sub>a-2</sub> (3%<E<6%)
Breaking load (225x400mm)	EN ISO 10545-4	> 750 N
Frost resistance	EN ISO 10545-12	Fulfilled
Resistance to thermal shock	EN ISO 10545-9	Fulfilled
Impact resistance (by measurement of coefficient of restitution)	EN ISO 10545-5	0.7-0.9
Fire resistance	-	Clase A1
Stain resistance	EN ISO 10545-14	Group 5 (Glazed)
Chemical resistance	EN ISO 10545-13	Group GA (Glazed)
Linear thermal expansion	EN ISO 10545-8	$5.75 \cdot 10^{-6} K^{-1} (\pm 1)$

## Tolerances and dimensions

Weight	-	2.5 kg/piece $\pm 0.5$ kg
Width	In extruding direction	$\pm 4.0$ mm
Height	Opposite to extruding direction	$\pm 2.0$ mm
Thickness	EN ISO 10545-2	13.0 mm $\pm 1.0$ mm
Straightness (in extruding direction)	EN ISO 10545-2	$\pm 1.5$ mm
Ortogonalit	EN ISO 10545-2	$\pm 2.0$ mm
Flatness		$\pm 2.0$ mm